


Description

Available in high power packages, the ITO-3P and TO-3P package.


Features

- $I_{GT\ max.} = 50\ mA$
- Low thermal resistance with clip bonding
- Max. blocking voltage = $V_{DRM}, V_{RRM} = 800V$



Applications

- General purpose AC switch control
- Control loads in Motor, Fan, and Pump.
- Solenoid drivers
- LED Dimming
- Inrush current limiting circuits



Absolute Maximum Ratings ($T_A=25^\circ C$)

Rating		Symbol	Value
Peak repetitive off-state voltage (50Hz to 60Hz; Gate open) (Note 1)		V_{DRM} V_{RRM}	800V
On-state RMS current (180° sine wave)		$I_{T(RMS)}$	55A
Non repetitive surge peak on-state current (full cycle, $T_{initial} = 25^\circ C$)	$F=50Hz, t=10ms$	I_{TSM}	300A
I^2t Value for fusing	$t_p=10ms$	I^2t	1800A ² s
Critical rate of rise of on-state current $I_G=2I_{GT}$	$F=120Hz, T_J=125^\circ C$	di/dt	200A/ μs
Non repetitive surge peak off-state voltage	$t_p=10ms, T_J=25^\circ C$	V_{DSM}/V_{RSM}	$V_{DRM}/V_{RRM}+100V$
Peak gate current	$t_p=20\mu s, T_J=125^\circ C$	I_{GM}	8A
Average gate power dissipation	$T_J=125^\circ C$	$P_{G(AV)}$	1W
Storage junction temperature range		T_{STG}	-40°C to +150°C
Operating junction temperature range		T_J	-40°C to +125°C

Note:

1. V_{DRM} and V_{RRM} for all types can be applied on a continuous basis.

Blocking voltages shall not be tested with a constant current source such that the voltage ratings of the devices are exceeded.

Electrical Characteristics ($T_J=25^{\circ}\text{C}$, unless otherwise specified)

Parameter	Symbol	Value
$V_D=12\text{V}, R_L=33\Omega$	I_{GT}	10mA~50mA
$V_D=V_{DRM}, R_L=100\Omega, T_J=125^{\circ}\text{C}$	$V_{GD \text{ Min.}}$	0.2V
$I_T=500\text{mA}$	$I_{H \text{ Max.}}^{(1)}$	100mA
$I_G=1.2I_{GT}$	$I_{L \text{ Max.}}$	125mA
$V_D=67\%V_{DRM}$ gate open, $T_J=125^{\circ}\text{C}$	$dv/dt \text{ Min.}^{(1)}$	1500V/ μs


1. for both polarities of A2 referenced to A1

Static Characteristics

Test conditions	Symbol	Value
$I_{TM}=55\text{A}, t_p=380\mu\text{s}, T_J=25^{\circ}\text{C}$	$V_T \text{ Max.}^{(1)}$	1.6V
Threshold voltage, $T_J=125^{\circ}\text{C}$	$V_{t0 \text{ Max.}}^{(1)}$	0.85V
Dynamic resistance, $T_J=125^{\circ}\text{C}$	$R_D \text{ Max.}^{(1)}$	8m Ω
$V_{DRM}=V_{RRM}, T_J=25^{\circ}\text{C}$	$I_{DRM \text{ Max.}}$	5 μA
$V_{DRM}=V_{RRM}, T_J=125^{\circ}\text{C}$	$I_{RRM \text{ Max.}}$	8mA

1. for both polarities of A2 referenced to A1

Part Number Code




Ordering Information

Part Number	Marking	Package
LC55P-08MS	LC55P-08MS	TO-3P
LC55V-08MS	LC55V-08MS	ITO-3P

Dimensions

TO-3P	Symbol	Millimeters	
		Min.	Max.
	A	14.9	15.35
	B	4.1	4.65
	C	20.21	20.75
	D	1.12	1.32
	E	5.35	5.62
	H	7.85	8.22
	K	2.71	2.92
	L	2.5	3.2
	L1	15.02	15.55
	T	4.38	4.65
	T1	1.42	1.62
	T2	0.52	0.68
	ΦR	4.12	4.31

Dimensions

ITO-3P	Symbol	Millimeters	
		Min.	Max.
	A	14.9	15.35
	B	4.1	4.65
	C	20.21	20.75
	D	1.12	1.32
	E	5.35	5.62
	H	7.85	8.22
	K	2.71	2.92
	L	2.5	3.2
	L1	15.02	15.55
	T	4.38	4.65
	T1	1.42	1.62
	T2	0.52	0.68
	ΦR	4.12	4.31

Important Notice and Disclaimer

LLOWN has used reasonable care in preparing the information included in this document, but LLOWN does not warrant that such information is error free. LLOWN assumes no liability whatsoever for any damages incurred by you resulting from errors in or omissions from the information included herein.

LLOWN no warranty, representation or guarantee regarding the documents, circuits and products specification, LLOWN reservation rights to make changes for any documents, products, circuits and specifications at any time without notice.

Purchasers are solely responsible for the choice, selection and use of the LLOWN products and services described herein, and LLOWN assumes no liability whatsoever relating to the choice, selection or use of the products and services described herein.

No license, express or implied, by implication or otherwise under any intellectual property rights of LLOWN.

Resale of LLOWN products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by LLOWN for the LLOWN product or service described herein and shall not create or extend in any manner whatsoever, any liability of LLOWN.