

Description

The LY236CA05UL is a ultra low capacitance TVS array, utilizing leading monolithic silicon technology to provide fast response time and low ESD clamping voltage, making this device an ideal solution for protecting voltage sensitive high-speed data lines. It complies with IEC 61000-4-2 (ESD), $\pm 30\text{kV}$ air and $\pm 30\text{kV}$ contact discharge. It is assembled into a lead-free SOT23-6 package. The low capacitance array make it ideal for four high speed data and transmission line.


Features

- Low clamping voltage
- Ultra low leakage current
- Operating voltage: 5V
- RoHS compliant
- IEC-61000-4-2 ESD $\pm 30\text{kV}$ Air, $\pm 30\text{kV}$ Contact
- Packaging: 7 inch reel, 3000pcs/reel


Applications

- USB2.0 Power and Data lines
- Video Graphic Cards
- Notebooks and PC Computers
- Digital Visual Interface (DVI)
- Monitors and Flat Panel Displays

Pin Configuration and Marking



Circuit and Pin Schematic



Absolute Maximum Ratings ($T_A=25^\circ\text{C}$)

Parameter	Symbol	Value
Peak Pulse Power (8/20μs)	P_{PP}	300W
Peak Pulse Current (8/20μs)	I_{PP}	12A
ESD per IEC 61000-4-2 (Air) ESD per IEC 61000-4-2 (Contact)	V_{ESD}	±30kV ±30kV
Ambient Temperature Range	T_A	-55°C to +125°C
Storage Temperature Range	T_{STG}	-55°C to +150°C

Electrical Characteristics ($T_A=25^\circ\text{C}$)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.
Reverse Working Voltage	V_{RWM}		-	-	5V
Breakdown Voltage	V_{BR}	$I_T = 1\text{mA}$	6.0V	-	-
Reverse Leakage Current	I_R	$V_{RWM} = 5\text{V}$	-	-	0.2μA
Clamping Voltage	V_C	$I_{PP} = 1\text{A}$ (8/20μs)	-	-	10V
		$I_{PP} = 12\text{A}$ (8/20μs)	-	-	25V
Junction Capacitance	C_J	$V_R = 0\text{V}$, $f = 1\text{MHz}$, between I/O pins	-	1.5pF	-
		$V_R = 0\text{V}$, $f = 1\text{MHz}$, any I/O to ground	-	3.0pF	-

Typical Characteristic Curves ($T_A=25^\circ\text{C}$)

Figure 1. Peak Pulse Power Rating Curve




Figure 2. Pulse Derating Curve




Figure 3. Clamping Voltage vs. Peak Pulse Current




Figure 4. Junction Capacitance vs. Reverse Voltage




Figure 5. Pulse Waveform (8/20μs)






Figure 6. Pulse Waveform (IEC61000-4-2)




Soldering Parameters

Reflow Soldering



Profile Feature	Pb-Free Assembly
Average ramp-up rate (T_L to T_P)	3°C/second max.
Preheat	
-Temperature Min ($T_{S\ min}$)	150°C
-Temperature Max ($T_{S\ max}$)	200°C
-Time (min to max) (t_s)	60-180 seconds
$T_{S\ max}$ to T_L	
-Ramp-up Rate	3°C/second max.
Time maintained above:	
-Temperature (T_L)	217°C
-Time (t_L)	60-150 seconds
Peak Temperature (T_P)	260°C
Time within 5°C of actual Peak Temperature (t_P)	20-40 seconds
Ramp-down Rate	6°C/second max.
Time 25°C to Peak Temperature	8 minutes max.

Dimensions (SOT23-6)



Recommended Solder Pad Layout (mm)

Symbol	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	2.80	3.10	0.110	0.122
B	2.60	3.00	0.102	0.118
B1	1.50	1.75	0.059	0.069
C	0.25	0.50	0.010	0.020
D	0.95 BSC		0.037 BSC	
D1	1.90 BSC		0.075 BSC	
H	0.90	1.45	0.035	0.057
H1	0.00	0.15	0.000	0.006
H2	0.90	1.30	0.035	0.051
t	0.08	0.22	0.003	0.009